

- **Multi Split Combination Possibility:**

- A single outdoor unit enables air conditioning of up to two separate rooms for CU-2Z35TBE, CU-2Z41TBE, CU-2Z50TBE.

| Connectable Indoor Unit |   |              | Outdoor Unit |               |            |               |            |               |
|-------------------------|---|--------------|--------------|---------------|------------|---------------|------------|---------------|
|                         |   |              | CU-2Z35TBE   |               | CU-2Z41TBE |               | CU-2Z50TBE |               |
|                         |   |              | A            | B             | A          | B             | A          | B             |
| Wall                    | 1.6kW   | CS-MZ16TKE   | •            | •             | •          | •             | •          | •             |
|                         |   | CS-MTZ16TKE  |              |               |            |               |            |               |
|                         | 2.0kW   | CS-Z20TKEW   |              |               |            |               |            |               |
|                         |   | CS-XZ20TKEW  | •            | •             | •          | •             | •          | •             |
|                         |   | CS-TZ20TKEW  |              |               |            |               |            |               |
|                         |   | CS-TE20TKEW  |              |               |            |               |            |               |
|                         | 2.5kW   | CS-Z25TKEW   |              |               |            |               |            |               |
|                         |   | CS-XZ25TKEW  |              |               |            |               |            |               |
|                         |   | CS-TZ25TKEW  | •            | •             | •          | •             | •          | •             |
|                         |   | CS-TE25TKEW  |              |               |            |               |            |               |
|                         |   | CS-E9PD3EA   |              |               |            |               |            |               |
|                         |   | CS-E9PB4EA   |              |               |            |               |            |               |
|                         | 3.5kW   | CS-Z35TKEW   |              |               |            |               |            |               |
|                         |   | CS-XZ35TKEW  |              |               |            |               |            |               |
|                         |   | CS-TZ35TKEW  | •            | -             | •          | -             | •          | •             |
|                         |   | CS-TE35TKEW  |              |               |            |               |            |               |
|                         |   | CS-E12QD3EAW |              |               |            |               |            |               |
|                         |   | CS-E12PB4EA  |              |               |            |               |            |               |
|                         | 4.2kW   | CS-Z42TKEW   |              |               |            |               |            |               |
|                         |   | CS-TZ42TKEW  | •            | -             | •          | -             | •          | -             |
|                         |   | CS-TE42TKEW  |              |               |            |               |            |               |
|                         | 5.0kW   | CS-Z50TKEW   |              |               |            |               |            |               |
|                         |   | CS-XZ50TKEW  |              |               |            |               |            |               |
|                         |   | CS-TZ50TKEW  | •            | -             | •          | -             | •          | -             |
|                         |   | CS-TE50TKEW  |              |               |            |               |            |               |
|                         |   | CS-E18RD3EAW |              |               |            |               |            |               |
|                         |   | CS-E18RB4EAW |              |               |            |               |            |               |
|                         | Capacity range of connectable indoor units          |              |              | 3.2kW ~ 6.0kW |            | 3.2kW ~ 6.0kW |            | 3.2kW ~ 7.7kW |
| Pipe Length             | 1-room maximum pipe length (m)                      |              | 20           |               | 20         |               | 20         |               |
|                         | Allowable elevation (m)                             |              | 10           |               | 10         |               | 10         |               |
|                         | Total allowable pipe length (m)                     |              | 30           |               | 30         |               | 30         |               |
|                         | Total pipe length for maximum chargeless length (m) |              | 20           |               | 20         |               | 20         |               |
|                         | Additional gas amount over chargeless length (g/m)  |              | 15           |               | 15         |               | 15         |               |

- Indoor Unit : CS-MZ/Z/XZ wall mount series
- Outdoor Unit : CU-2Z35TBE

| Indoor unit capacity Cooling | Total     | Cooling Capacity (kW) |        |       |           | Input Power (W) |            | EER        |            | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |           |     |
|------------------------------|-----------|-----------------------|--------|-------|-----------|-----------------|------------|------------|------------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|-----------|-----|
|                              |           | Room A                | Room B | Total | min ~ max | Rating          | min ~ max  | WW         | CLASS      |                                 |                   | Pdesign (kW) | SEER |       | Annual Consumption (kWh) |                             |           |     |
|                              |           |                       |        |       |           |                 |            |            |            |                                 |                   |              | WW   | CLASS |                          |                             |           |     |
| 1 Room                       | 1.6       | 1.6                   |        | 1.60  |           | 1.60            | 1.1 ~ 2.3  | 410        | 220 ~ 600  | 3.90                            | A                 | 205          | 1.95 | -     | -                        | -                           | -         | 1.0 |
|                              | 2.0       | 2.0                   |        | 2.00  |           | 2.00            | 1.1 ~ 2.9  | 520        | 220 ~ 770  | 3.85                            | A                 | 260          | 2.45 | -     | -                        | -                           | -         | 1.3 |
|                              | 2.5       | 2.5                   |        | 2.50  |           | 2.50            | 1.1 ~ 3.5  | 670        | 220 ~ 1000 | 3.73                            | A                 | 335          | 3.15 | -     | -                        | -                           | -         | 1.5 |
|                              | 3.5       | 3.5                   |        | 3.50  |           | 3.50            | 1.1 ~ 4.0  | 1010       | 220 ~ 1220 | 3.47                            | A                 | 505          | 4.70 | -     | -                        | -                           | -         | 2.0 |
| 2 Room                       | 1.6 + 1.6 | 3.2                   | 1.60   | 1.60  | 3.20      | 1.5 ~ 4.0       | 650        | 250 ~ 1000 | 4.92       | A                               | 325               | 3.05         | 3.20 | 8.50  | A+++                     | 132                         | 1.0 + 1.0 |     |
|                              | 1.6 + 2.0 | 3.6                   | 1.55   | 1.95  | 3.50      | 1.5 ~ 4.5       | 720        | 250 ~ 1100 | 4.86       | A                               | 360               | 3.35         | 3.50 | 8.50  | A+++                     | 144                         | 1.0 + 1.3 |     |
|                              | 1.6 + 2.5 | 4.1                   | 1.35   | 2.15  | 3.50      | 1.5 ~ 4.5       | 720        | 250 ~ 1100 | 4.86       | A                               | 360               | 3.35         | 3.50 | 8.50  | A+++                     | 144                         | 0.9 + 1.4 |     |
|                              | 1.6 + 3.5 | 5.1                   | 1.10   | 2.40  | 3.50      | 1.5 ~ 4.5       | 720        | 250 ~ 1100 | 4.86       | A                               | 360               | 3.35         | 3.50 | 8.50  | A+++                     | 144                         | 0.7 + 1.5 |     |
|                              | 2.0 + 2.0 | 4.0                   | 1.75   | 1.75  | 3.50      | 1.5 ~ 4.5       | 720        | 250 ~ 1100 | 4.86       | A                               | 360               | 3.35         | 3.50 | 8.50  | A+++                     | 144                         | 1.1 + 1.1 |     |
|                              | 2.0 + 2.5 | 4.5                   | 1.55   | 1.95  | 3.50      | 1.5 ~ 4.5       | 720        | 250 ~ 1100 | 4.86       | A                               | 360               | 3.35         | 3.50 | 8.50  | A+++                     | 144                         | 1.0 + 1.3 |     |
|                              | 2.0 + 3.5 | 5.5                   | 1.25   | 2.25  | 3.50      | 1.5 ~ 4.5       | 690        | 250 ~ 1050 | 5.07       | A                               | 345               | 3.25         | 3.50 | 8.50  | A+++                     | 144                         | 0.8 + 1.5 |     |
|                              | 2.5 + 2.5 | 5.0                   | 1.75   | 1.75  | 3.50      | 1.5 ~ 4.5       | 690        | 250 ~ 1050 | 5.07       | A                               | 345               | 3.25         | 3.50 | 8.50  | A+++                     | 144                         | 1.1 + 1.1 |     |
| 2.5 + 3.5                    | 6.0       | 1.45                  | 2.05   | 3.50  | 1.5 ~ 4.5 | 690             | 250 ~ 1050 | 5.07       | A          | 345                             | 3.25              | 3.50         | 8.50 | A+++  | 144                      | 0.9 + 1.3                   |           |     |

| Indoor unit capacity Heating | Total     | Heating Capacity (kW) |        |       |           | Input Power (W) |            | EER        |            | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |   |
|------------------------------|-----------|-----------------------|--------|-------|-----------|-----------------|------------|------------|------------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|---|
|                              |           | Room A                | Room B | Total | min ~ max | Rating          | min ~ max  | WW         | CLASS      |                                 |                   | Pdesign (kW) | SCOP |       | Annual Consumption (kWh) |                             |   |
|                              |           |                       |        |       |           |                 |            |            |            |                                 |                   |              | WW   | CLASS |                          |                             |   |
| 1 Room                       | 1.6       | 1.6                   |        | 2.60  |           | 2.60            | 0.7 ~ 3.8  | 690        | 170 ~ 1110 | 3.77                            | A                 | 345          | 3.20 | -     | -                        | -                           | - |
|                              | 2.0       | 2.0                   |        | 3.20  |           | 3.20            | 0.7 ~ 4.8  | 850        | 170 ~ 1410 | 3.76                            | A                 | 425          | 3.95 | -     | -                        | -                           | - |
|                              | 2.5       | 2.5                   |        | 3.60  |           | 3.60            | 0.7 ~ 5.5  | 1030       | 170 ~ 1700 | 3.50                            | B                 | 515          | 4.75 | -     | -                        | -                           | - |
|                              | 3.5       | 3.5                   |        | 4.20  |           | 4.20            | 0.7 ~ 5.6  | 1220       | 170 ~ 1680 | 3.44                            | B                 | 610          | 5.65 | -     | -                        | -                           | - |
| 2 Room                       | 1.6 + 1.6 | 3.2                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.00 | 4.60  | A++                      | 913                         |   |
|                              | 1.6 + 2.0 | 3.6                   | 1.85   | 2.35  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 1.6 + 2.5 | 4.1                   | 1.65   | 2.55  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 1.6 + 3.5 | 5.1                   | 1.30   | 2.90  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 2.0 + 2.0 | 4.0                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 2.0 + 2.5 | 4.5                   | 1.85   | 2.35  | 4.20      | 1.1 ~ 5.6       | 860        | 210 ~ 1340 | 4.88       | A                               | 430               | 4.00         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 2.0 + 3.5 | 5.5                   | 1.55   | 2.65  | 4.20      | 1.1 ~ 5.6       | 840        | 210 ~ 1290 | 5.00       | A                               | 420               | 3.90         | 3.20 | 4.60  | A++                      | 974                         |   |
|                              | 2.5 + 2.5 | 5.0                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 840        | 210 ~ 1290 | 5.00       | A                               | 420               | 3.90         | 3.20 | 4.60  | A++                      | 974                         |   |
| 2.5 + 3.5                    | 6.0       | 1.75                  | 2.45   | 4.20  | 1.1 ~ 5.6 | 840             | 210 ~ 1290 | 5.00       | A          | 420                             | 3.90              | 3.20         | 4.60 | A++   | 974                      |                             |   |

- Indoor Unit : Combination of all wall mount series (CS-MZ/Z/XZ/MTZ/TZ/TE)
- Outdoor Unit : CU-2Z35TBE

| Indoor unit capacity Cooling |           | Total | Cooling Capacity (kW) |        |           |           | Input Power (W) |            | EER  |       | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |
|------------------------------|-----------|-------|-----------------------|--------|-----------|-----------|-----------------|------------|------|-------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|
|                              |           |       | Room A                | Room B | Total     | min ~ max | Rating          | min ~ max  | W/W  | CLASS |                                 |                   | Pdesign (kW) | SEER |       | Annual Consumption (kWh) |                             |
|                              |           |       |                       |        |           |           |                 |            |      |       |                                 |                   |              | W/W  | CLASS |                          |                             |
| 1 Room                       | 1.6       | 1.6   | 1.60                  |        | 1.60      | 1.1 ~ 2.3 | 430             | 220 ~ 620  | 3.72 | A     | 215                             | 2.05              | -            | -    | -     |                          | 1.0                         |
|                              | 2.0       | 2.0   | 2.00                  |        | 2.00      | 1.1 ~ 2.9 | 540             | 220 ~ 790  | 3.70 | A     | 270                             | 2.55              | -            | -    | -     |                          | 1.3                         |
|                              | 2.5       | 2.5   | 2.50                  |        | 2.50      | 1.1 ~ 3.5 | 690             | 220 ~ 1020 | 3.62 | A     | 345                             | 3.25              | -            | -    | -     |                          | 1.5                         |
|                              | 3.5       | 3.5   | 3.50                  |        | 3.50      | 1.1 ~ 4.0 | 1030            | 220 ~ 1240 | 3.40 | A     | 515                             | 4.80              | -            | -    | -     |                          | 2.0                         |
| 2 Room                       | 1.6 + 1.6 | 3.2   | 1.60                  | 1.60   | 3.20      | 1.5 ~ 4.0 | 690             | 250 ~ 1040 | 4.64 | A     | 345                             | 3.25              | 3.20         | 8.50 | A+++  | 132                      | 1.0 + 1.0                   |
|                              | 1.6 + 2.0 | 3.6   | 1.55                  | 1.95   | 3.50      | 1.5 ~ 4.5 | 760             | 250 ~ 1140 | 4.61 | A     | 380                             | 3.55              | 3.50         | 8.50 | A+++  | 144                      | 1.0 + 1.3                   |
|                              | 1.6 + 2.5 | 4.1   | 1.35                  | 2.15   | 3.50      | 1.5 ~ 4.5 | 760             | 250 ~ 1140 | 4.61 | A     | 380                             | 3.55              | 3.50         | 8.50 | A+++  | 144                      | 0.9 + 1.4                   |
|                              | 1.6 + 3.5 | 5.1   | 1.10                  | 2.40   | 3.50      | 1.5 ~ 4.5 | 760             | 250 ~ 1140 | 4.61 | A     | 380                             | 3.55              | 3.50         | 8.50 | A+++  | 144                      | 0.7 + 1.5                   |
|                              | 2.0 + 2.0 | 4.0   | 1.75                  | 1.75   | 3.50      | 1.5 ~ 4.5 | 760             | 250 ~ 1140 | 4.61 | A     | 380                             | 3.55              | 3.50         | 8.50 | A+++  | 144                      | 1.1 + 1.1                   |
|                              | 2.0 + 2.5 | 4.5   | 1.55                  | 1.95   | 3.50      | 1.5 ~ 4.5 | 760             | 250 ~ 1140 | 4.61 | A     | 380                             | 3.55              | 3.50         | 8.50 | A+++  | 144                      | 1.0 + 1.3                   |
|                              | 2.0 + 3.5 | 5.5   | 1.25                  | 2.25   | 3.50      | 1.5 ~ 4.5 | 730             | 250 ~ 1090 | 4.79 | A     | 365                             | 3.40              | 3.50         | 8.50 | A+++  | 144                      | 0.8 + 1.5                   |
|                              | 2.5 + 2.5 | 5.0   | 1.75                  | 1.75   | 3.50      | 1.5 ~ 4.5 | 730             | 250 ~ 1090 | 4.79 | A     | 365                             | 3.40              | 3.50         | 8.50 | A+++  | 144                      | 1.1 + 1.1                   |
| 2.5 + 3.5                    | 6.0       | 1.45  | 2.05                  | 3.50   | 1.5 ~ 4.5 | 730       | 250 ~ 1090      | 4.79       | A    | 365   | 3.40                            | 3.50              | 8.50         | A+++ | 144   | 0.9 + 1.3                |                             |

| Indoor unit capacity Heating |           | Total | Heating Capacity (kW) |        |           |           | Input Power (W) |            | EER  |       | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |
|------------------------------|-----------|-------|-----------------------|--------|-----------|-----------|-----------------|------------|------|-------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|
|                              |           |       | Room A                | Room B | Total     | min ~ max | Rating          | min ~ max  | W/W  | CLASS |                                 |                   | Pdesign (kW) | SCOP |       | Annual Consumption (kWh) |                             |
|                              |           |       |                       |        |           |           |                 |            |      |       |                                 |                   |              | W/W  | CLASS |                          |                             |
| 1 Room                       | 1.6       | 1.6   | 2.60                  |        | 2.60      | 0.7 ~ 3.8 | 730             | 170 ~ 1150 | 3.56 | A     | 365                             | 3.40              | -            | -    | -     |                          |                             |
|                              | 2.0       | 2.0   | 3.20                  |        | 3.20      | 0.7 ~ 4.8 | 890             | 170 ~ 1450 | 3.60 | A     | 445                             | 4.10              | -            | -    | -     |                          |                             |
|                              | 2.5       | 2.5   | 3.60                  |        | 3.60      | 0.7 ~ 5.5 | 1070            | 170 ~ 1740 | 3.36 | B     | 535                             | 4.95              | -            | -    | -     |                          |                             |
|                              | 3.5       | 3.5   | 4.20                  |        | 4.20      | 0.7 ~ 5.6 | 1260            | 170 ~ 1720 | 3.33 | B     | 630                             | 5.85              | -            | -    | -     |                          |                             |
| 2 Room                       | 1.6 + 1.6 | 3.2   | 2.10                  | 2.10   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.00         | 4.10 | A+    | 1024                     |                             |
|                              | 1.6 + 2.0 | 3.6   | 1.85                  | 2.35   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 1.6 + 2.5 | 4.1   | 1.65                  | 2.55   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 1.6 + 3.5 | 5.1   | 1.30                  | 2.90   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 2.0 + 2.0 | 4.0   | 2.10                  | 2.10   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 2.0 + 2.5 | 4.5   | 1.85                  | 2.35   | 4.20      | 1.1 ~ 5.6 | 940             | 210 ~ 1420 | 4.47 | A     | 470                             | 4.35              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 2.0 + 3.5 | 5.5   | 1.55                  | 2.65   | 4.20      | 1.1 ~ 5.6 | 920             | 210 ~ 1370 | 4.57 | A     | 460                             | 4.25              | 3.20         | 4.10 | A+    | 1093                     |                             |
|                              | 2.5 + 2.5 | 5.0   | 2.10                  | 2.10   | 4.20      | 1.1 ~ 5.6 | 920             | 210 ~ 1370 | 4.57 | A     | 460                             | 4.25              | 3.20         | 4.10 | A+    | 1093                     |                             |
| 2.5 + 3.5                    | 6.0       | 1.75  | 2.45                  | 4.20   | 1.1 ~ 5.6 | 920       | 210 ~ 1370      | 4.57       | A    | 460   | 4.25                            | 3.20              | 4.10         | A+   | 1093  |                          |                             |

- Indoor Unit : Combination of all type of wall and non-wall series (CS-MZ/Z/XZ/MTZ/TZ/TE/E)
- Outdoor Unit : CU-2Z35TBE

| Indoor unit capacity Cooling | Total     | Cooling Capacity (kW) |        |       |           | Input Power (W) |            | EER        |            | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |           |
|------------------------------|-----------|-----------------------|--------|-------|-----------|-----------------|------------|------------|------------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|-----------|
|                              |           | Room A                | Room B | Total | min ~ max | Rating          | min ~ max  | WW         | CLASS      |                                 |                   | Pdesign (kW) | SEER |       | Annual Consumption (kWh) |                             |           |
|                              |           |                       |        |       |           |                 |            |            |            |                                 |                   |              | WW   | CLASS |                          |                             |           |
| 1 Room                       | 1.6       | 1.6                   |        | 1.60  |           | 1.60            | 1.1 ~ 2.3  | 460        | 220 ~ 650  | 3.48                            | A                 | 230          | 2.20 | -     | -                        | -                           | 1.0       |
|                              | 2.0       | 2.0                   |        | 2.00  |           | 2.00            | 1.1 ~ 2.9  | 570        | 220 ~ 820  | 3.51                            | A                 | 285          | 2.70 | -     | -                        | -                           | 1.3       |
|                              | 2.5       | 2.5                   |        | 2.50  |           | 2.50            | 1.1 ~ 3.5  | 720        | 220 ~ 1050 | 3.47                            | A                 | 360          | 3.40 | -     | -                        | -                           | 1.5       |
|                              | 3.5       | 3.5                   |        | 3.50  |           | 3.50            | 1.1 ~ 4.0  | 1060       | 220 ~ 1270 | 3.30                            | A                 | 530          | 4.95 | -     | -                        | -                           | 2.0       |
| 2 Room                       | 1.6 + 1.6 | 3.2                   | 1.60   | 1.60  | 3.20      | 1.5 ~ 4.0       | 750        | 250 ~ 1100 | 4.27       | A                               | 375               | 3.50         | 3.20 | 7.00  | A++                      | 160                         | 1.0 + 1.0 |
|                              | 1.6 + 2.0 | 3.6                   | 1.55   | 1.95  | 3.50      | 1.5 ~ 4.5       | 820        | 250 ~ 1200 | 4.27       | A                               | 410               | 3.85         | 3.50 | 7.00  | A++                      | 175                         | 1.0 + 1.3 |
|                              | 1.6 + 2.5 | 4.1                   | 1.35   | 2.15  | 3.50      | 1.5 ~ 4.5       | 820        | 250 ~ 1200 | 4.27       | A                               | 410               | 3.85         | 3.50 | 7.00  | A++                      | 175                         | 0.9 + 1.4 |
|                              | 1.6 + 3.5 | 5.1                   | 1.10   | 2.40  | 3.50      | 1.5 ~ 4.5       | 820        | 250 ~ 1200 | 4.27       | A                               | 410               | 3.85         | 3.50 | 7.00  | A++                      | 175                         | 0.7 + 1.5 |
|                              | 2.0 + 2.0 | 4.0                   | 1.75   | 1.75  | 3.50      | 1.5 ~ 4.5       | 820        | 250 ~ 1200 | 4.27       | A                               | 410               | 3.85         | 3.50 | 7.00  | A++                      | 175                         | 1.1 + 1.1 |
|                              | 2.0 + 2.5 | 4.5                   | 1.55   | 1.95  | 3.50      | 1.5 ~ 4.5       | 820        | 250 ~ 1200 | 4.27       | A                               | 410               | 3.85         | 3.50 | 7.00  | A++                      | 175                         | 1.0 + 1.3 |
|                              | 2.0 + 3.5 | 5.5                   | 1.25   | 2.25  | 3.50      | 1.5 ~ 4.5       | 790        | 250 ~ 1150 | 4.43       | A                               | 395               | 3.70         | 3.50 | 7.00  | A++                      | 175                         | 0.8 + 1.5 |
|                              | 2.5 + 2.5 | 5.0                   | 1.75   | 1.75  | 3.50      | 1.5 ~ 4.5       | 790        | 250 ~ 1150 | 4.43       | A                               | 395               | 3.70         | 3.50 | 7.00  | A++                      | 175                         | 1.1 + 1.1 |
| 2.5 + 3.5                    | 6.0       | 1.45                  | 2.05   | 3.50  | 1.5 ~ 4.5 | 790             | 250 ~ 1150 | 4.43       | A          | 395                             | 3.70              | 3.50         | 7.00 | A++   | 175                      | 0.9 + 1.3                   |           |

| Indoor unit capacity Heating | Total     | Heating Capacity (kW) |        |       |           | Input Power (W) |            | EER        |            | ANNUAL ENERGY CONSUMPTION (kWh) | Current, 230V (A) | ERP          |      |       |                          | MOISTURE REMOVAL VOLUME l/h |  |
|------------------------------|-----------|-----------------------|--------|-------|-----------|-----------------|------------|------------|------------|---------------------------------|-------------------|--------------|------|-------|--------------------------|-----------------------------|--|
|                              |           | Room A                | Room B | Total | min ~ max | Rating          | min ~ max  | WW         | CLASS      |                                 |                   | Pdesign (kW) | SCOP |       | Annual Consumption (kWh) |                             |  |
|                              |           |                       |        |       |           |                 |            |            |            |                                 |                   |              | WW   | CLASS |                          |                             |  |
| 1 Room                       | 1.6       | 1.6                   |        | 2.60  |           | 2.60            | 0.7 ~ 3.8  | 790        | 170 ~ 1210 | 3.29                            | A                 | 395          | 3.65 | -     | -                        | -                           |  |
|                              | 2.0       | 2.0                   |        | 3.20  |           | 3.20            | 0.7 ~ 4.8  | 950        | 170 ~ 1510 | 3.37                            | A                 | 475          | 4.40 | -     | -                        | -                           |  |
|                              | 2.5       | 2.5                   |        | 3.60  |           | 3.60            | 0.7 ~ 5.5  | 1130       | 170 ~ 1800 | 3.19                            | B                 | 565          | 5.25 | -     | -                        | -                           |  |
|                              | 3.5       | 3.5                   |        | 4.20  |           | 4.20            | 0.7 ~ 5.6  | 1320       | 170 ~ 1780 | 3.18                            | B                 | 660          | 6.10 | -     | -                        | -                           |  |
| 2 Room                       | 1.6 + 1.6 | 3.2                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.00 | 3.80  | A                        | 1105                        |  |
|                              | 1.6 + 2.0 | 3.6                   | 1.85   | 2.35  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 1.6 + 2.5 | 4.1                   | 1.65   | 2.55  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 1.6 + 3.5 | 5.1                   | 1.30   | 2.90  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 2.0 + 2.0 | 4.0                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 2.0 + 2.5 | 4.5                   | 1.85   | 2.35  | 4.20      | 1.1 ~ 5.6       | 1060       | 210 ~ 1540 | 3.96       | A                               | 530               | 4.90         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 2.0 + 3.5 | 5.5                   | 1.55   | 2.65  | 4.20      | 1.1 ~ 5.6       | 1040       | 210 ~ 1490 | 4.04       | A                               | 520               | 4.80         | 3.20 | 3.80  | A                        | 1179                        |  |
|                              | 2.5 + 2.5 | 5.0                   | 2.10   | 2.10  | 4.20      | 1.1 ~ 5.6       | 1040       | 210 ~ 1490 | 4.04       | A                               | 520               | 4.80         | 3.20 | 3.80  | A                        | 1179                        |  |
| 2.5 + 3.5                    | 6.0       | 1.75                  | 2.45   | 4.20  | 1.1 ~ 5.6 | 1040            | 210 ~ 1490 | 4.04       | A          | 520                             | 4.80              | 3.20         | 3.80 | A     | 1179                     |                             |  |