


5 ROOMS MULTI

AOYG36KBTA5



AOYG36KBTA5



Point High energy saving

All models achieve high energy efficiency rank of A+++ for cooling and A++ for heating by using High efficiency DC twin rotary compressor.

Rank
Cooling
A+++
Heating
A++

SEER
8.5


SCOP
4.6




Highly Efficient DC Fan Motor




DC Inverter Control



Large Highly Efficient Heat Exchanger



Outdoor Unit



DC Twin Rotary Compressor

Point Space-saving installation

Multiple indoor units can be connected to 1 outdoor unit, and long piping connection is also possible.



Multiple Outdoor Units Required

Simple setting

Point Compact Design

Reduced footprint for the outdoor units allow for flexible installation

R410A model



R32 model



Width difference
-15.4 % !*
Footprint Difference
-28.0 % !*

*Compared with AOYG36LBLA5

Point Wide range of indoor units with various models

5 types / 41 models are lined up in the capacity range from 2.0 kW to 6.0 kW class. Wide range of requirements can be realised from in private homes, large offices and shops.

Middle and small capacity models are available. This makes it easier to install in small spaces.



Models equipped with the New R32 Refrigerant

Wall Mounted Designer Series



07-14 KETA and KETA-B

Wall Mounted Standard Series



07-14KMCC



07-14KGTB



18-24KMTB

Mini Duct



07-18KSLAP

Slim Duct



07-18KLLAP

Medium Static Pressure Duct



22KMLB

Compact Cassette



07-22KVLA

Floor



09-14KVCA

Ceiling



18-22KRTA

Model: AOYG36KBTA5




AOYG36KBTA5

Dimensions

(UNIT : MM)

AOYG36KBTA5



Specifications

Model No.		AOYG36KBTA5	
Power Source		Single phase, ~230V, 50Hz	
Recommended Fuse Size		25 Amp	
Rated Capacity (Min. - Max.)	Cooling	kW	9.5 (3.0-11.0)
	Heating		10.6 (3.5-12.0)
EER	Cooling	W/W	3.80
	Heating		4.50
COP	Cooling	dB(A)	52
	Heating		55
Sound Pressure Level (High)	Cooling	dB(A)	65
	Heating		68
Sound Power Level (High)	Cooling	m ³ /h	2,450/2,900
	Heating		
Airflow Rate			
Net Dimensions H × W × D		mm	884 × 820 × 315
Weight		kg(lbs)	59(130)
Connection Pipe Diameter	Liquid	mm	1/4 × 5
	Gas		3/8 × 3, 1/2 × 2 adapter [1/2 → 3/8] × 2 adapter [3/8 → 1/2] × 1
Max. Pipe Length*		Total / Each	75/25
Max. Height Difference	Between Outdoor Unit and Each Indoor Unit		15
	Between Indoor Unit		10
Operating Range	Cooling	°CDB	-10 to 46
	Heating		-15 to 24
Refrigerant	Type (Global Warming Potential)	R32 (675)	
	Charge	kg(CO ₂ eq-T)	2.5 (1.688)
Refrigerant Pre-Charge		m	40m
Additional Charge per meter		g	20g

*The length would not be applied when floor units are connected. For the detailed condition, please refer to the installation manual.

•Specifications and design are subject to change without notice for further improvement.
•Actual products' colors may be different from the colors shown in this printed material.

Distributed by :

FUJITSU GENERAL AIR CONDITIONING (UK) LTD
Unit 150 Centennial Park, Centennial Avenue, Elstree, Herts. WD6 3SG
www.fujitsu-general.com/uk

Tel: +44 (0)208 731 3450 Fax: +44 (0)208 731 3451