



FCAHG-H / RZAG-N *SkyAir Alpha-series*

R-32 **BLUEEVOLUTION**

360° air discharge for optimum efficiency and comfort

- › Combinations with Sky Air Alpha series ensures best in class quality, highest efficiency and performance
- › High COP cassette ensures top performance, great savings in energy consumption and a comfortable environment for commercial applications
- › Individual louvre control: flexibility to suit every room layout without changing the location of the unit
- › Modern style decoration panel is available in 4 different variations: white with grey louvers, full white, with black finishing or with Auto Cleaning panel
- › Automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs. 2 filters available: standard filter and finer mesh filter (for fine dust applications i.e. clothing shops)
- › Two optional intelligent sensors improve energy efficiency and comfort
- › No optional adapter needed for DIII-connection, link your unit directly into the wider building management system
- › Branch duct discharge allows to optimize air distribution in irregular shaped rooms or to supply air to small adjacent rooms
- › Reduced energy consumption thanks to specially developed small tube exchanger, DC fan motor and drain pump
- › Optional fresh air intake
- › Standard drain pump with 675mm lift increases flexibility and installation speed



FCAHG-H (Black)



FCAHG-H (White)



RZAG71-140N



BRC7FA532F/B (optional)



Madoka BRCIH52W



WI-FI CONTROL VIA APP



WI-FI ADAPTOR

AVAILABLE AS AN OPTION





FCAHG-H / RZAG-N

SkyAir Alpha-series

R-32 BLUEEVOLUTION


Indoor Units			Single Phase				3 Phase			
			FCAHG71H	FCAHG100H	FCAHG125H	FCAHG140H	FCAHG71H	FCAHG100H	FCAHG125H	FCAHG140H
Capacity	UK Total Cooling	kW	7.76	10.85	13.6	14.93	7.76	10.85	13.6	14.93
	UK Sensible Cooling	kW	5.32	7.44	9.30	10.25	5.32	7.44	9.30	10.25
	Nominal Cooling	kW	6.8	9.5	12.1	13.4	6.8	9.5	12.1	13.4
	Nominal Heating	kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++	-	-	A++	A++	-	-
	Pdesign	kW	6.8	9.5	12.1	13.4	6.8	9.5	12.1	13.4
	SEER		7.90	7.70	8.02	7.93	7.90	7.70	8.02	7.93
	ηs,c	%	-	-	318	314	-	-	318	314
Seasonal Efficiency (EN14825) HEATING	Annual Energy Consumption	kWh	301	432	905	1014	301	432	905	1014
	Energy Label		A++	A++	-	-	A++	A++	-	-
	Pdesign	kW	4.70	9.52	9.52	9.52	4.70	9.52	9.52	9.52
	SCOP		4.61	4.75	4.53	4.44	4.61	4.75	4.53	4.44
Air Flow Rate (Cooling)	ηs,h	%	-	-	178	175	-	-	178	175
	Annual Energy Consumption	kWh	1427	2805	2942	3002	1427	2805	2942	3002
	High / Med / Low	m³/sec	0.393 / 0.313 / 0.228	0.537 / 0.428 / 0.318	0.573 / 0.455 / 0.353	0.573 / 0.455 / 0.353	0.393 / 0.313 / 0.228	0.537 / 0.428 / 0.318	0.573 / 0.455 / 0.353	0.573 / 0.455 / 0.353
	Height	mm	288 (353)	288 (353)	288 (353)	288 (353)	288 (353)	288 (353)	288 (353)	288 (353)
Dimensions (with Decoration Panel)	Width	mm	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
	Depth	mm	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
Weight (with Decoration Panel)	kg	25 (30.5)	25 (30.5)	25 (30.5)	25 (30.5)	25 (30.5)	25 (30.5)	25 (30.5)	25 (30.5)	
Sound Pressure (Cooling)	High / Med / Low	dBA	36 / 33 / 29	44 / 39 / 33	45 / 40 / 35	45 / 41 / 37	36 / 33 / 29	44 / 39 / 33	45 / 40 / 35	45 / 41 / 37
Sound Pressure (Heating)	High / Med / Low	dBA	36 / 33 / 29	44 / 39 / 33	45 / 40 / 35	45 / 41 / 37	33 / 31 / 28	44 / 39 / 33	45 / 40 / 35	45 / 41 / 37
Sound Power (Cooling)		dBA	53	61	61	61	53	61	61	61

Outdoor Units			RZAG71NV1	RZAG100NV1	RZAG125NV1	RZAG140NV1	RZAG71NY1	RZAG100NY1	RZAG125NY1	RZAG140NY1
Dimensions	Height x Width x Depth	mm	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460	870 x 1100 x 460
Weight		kg	81	85	95	95	81	85	95	95
Electrical Details	Power Supply	1ph	1ph	1ph	1ph	3ph	3ph	3ph	3ph	3ph
	Maximum Input Current (MCA) A		17.7	22.2	27.5	27.5	11.1	14.9	15.0	15.0
	Max Fuse Size A		20	32	32	32.0	16.0	16.0	16.0	16.0
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)	3/8 (9.5) / 5/8 (15.9)
Pipework	Maximum Length	m	55	85	85	85	55	85	85	85
	Maximum Vertical Rise	m	30	30	30	30	30	30	30	30
	Precharged to	m	40	40	40	40	40	40	40	40
	Additional charge	g/m	35	35	35	35	35	35	35	35
	Holding charge	kg	3.2	3.2	3.7	3.7	3.2	3.2	3.7	3.7
Sound Pressure (Cooling)	Nom / Night Quiet	dBA	46 / 44	47 / 45	49 / 47	50 / 48	46 / 44	47 / 45	49 / 47	50 / 48
Sound Pressure (Heating)	Nom / Night Quiet	dBA	48 / 44	50 / 45	52 / 47	52 / 48	48 / 44	50 / 45	52 / 47	52 / 48
Sound Power (Cooling)		dBA	64	66	69	70	64	66	69	70
Operating Range (Cooling)	Min / Max	°CDB	-20 / 52	-20 / 52	-20 / 52	-20 / 52	-20 / 52	-20 / 52	-20 / 52	-20 / 52
Operating Range (Heating)	Min / Max	°CWB	-20 / 18	-20 / 18	-20 / 18	-20 / 18	-20 / 18	-20 / 18	-20 / 18	-20 / 18
Air Flow Rate (Cooling)	Nominal	m³/sec	1.133	1.117	1.333	1.450	1.133	1.117	1.333	1.450
Meets ETL criteria			•	•	•	•	•	•	•	•

Accessory Ref	Description
BYCQ140E	Decoration panel - White (Included as standard)
BYCQ140EB	Decoration panel - Black
BRP069C82	Wifi adaptor for connection to on-line controller
BRC1H52W	Wired touch screen remote controller - White (Included as standard)
BRC1H52S	Wired touch screen remote controller - Silver
BRC1H52K	Wired touch screen remote controller - Black
BRC7FA532F	Wireless remote controller (for white panel)
BRC7FA532FB	Wireless remote controller (for black panel)
BRYQ140B	Integral PIR sensor for roundflow decoration panel (for white panel)
BRYQ140BB	Integral PIR sensor for roundflow decoration panel (for black panel)
BYCQ140EGF	Auto Cleaning Deco Panel - White
BYCQ140EGFB	Auto Cleaning Deco Panel - Black
BYCQ140EW	Decoration Panel - Full White
EWHAR1	Extension wire - Required if Wifi Adaptor and Auto Cleaning panel are installed together
K.CGM	Condensing unit guard (1150 x 1150 x 650)

Accessory Ref	Description
K.CWBXL	Wall bracket (250kg, 660mm support arm)
K.DT2	Condensate drip tray for use with K.CWBXL
SB.K.RSS_RFC	Wireless room mounted temperature sensor and receiver
KDBHQ56B140	Sealing member for air discharge outlet
KDDP55C160-1	Fresh air intake kit for up to 20% fresh air (Part 1)
KDDP55D160-2	Fresh air intake kit for up to 20% fresh air (Part 2)
KLIC-DI	KNX Interface for Sky Air and VRV systems
KRCS01-7B	Remote room mounted temperature sensor
KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
RS-SE	Service and configuration tool for K.RSS
RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV. Duty rotation, Lead Lag control and heating interlock
RTD-20 and UK.FB2	Energy control PCB for Sky Air and VRV
RTD-NET and UK.FB2	Modbus interface PCB for Sky Air and VRV

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioning (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com