



FDXM-F9 / RZAG-A

Slim ducted unit,
with a height of only 200mm

- > Combination with new Mini Sky Air to achieve up to 50m total pipe run
- > Discretely concealed in the ceiling: only the suction and discharge grilles are visible
- > Compact dimensions, can easily be mounted in a ceiling void of only 240mm
- > Medium external static pressure up to 40Pa facilitates unit use with flexible ducts of varying lengths
- > Low energy consumption thanks to DC fan motor
- > Seasonal efficiency values up to A+ in cooling and heating

R-32 BLUEEVOLUTION



FDXM-F9



RZAG35A




BRC1H519W



BRC4C65
(optional)



BRP069A81
(optional)



WI-FI ADAPTOR
AVAILABLE AS AN OPTION

FDXM-F9 / RZAG-A

R-32 BLUEEVOLUTION

Indoor Units			FDXM35F9	FDXM50F9	FDXM60F9
Capacity	UK Total Cooling	kW	3.32	4.81	5.86
	UK Sensible Cooling	kW	2.26	3.08	3.97
	Nominal Cooling	kW	3.4	5.0	6.0
	Nominal Heating	kW	4.0	5.8	7.0
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+	A+	A+
	Pdesign	kW	3.4	5.0	6.0
	SEER		5.90	5.90	5.70
	Energy Label		A	A	A
Seasonal Efficiency (EN14825) HEATING	Pdesign	kW	2.9	4.0	4.6
	SCOP		3.90	3.90	3.90
	EER/COP		3.90 / 3.50	3.80 / 3.40	3.40 / 3.30
Nominal Efficiency					
Air Flow Rate (Cooling)	High / Nom / Low	m ³ /sec	0.145/0.133/0.121	0.263/0.243/0.221	0.266/0.246/0.225
External Static Pressure	Nominal	Pa	30	40	40
	Height	mm	200	200	200
	Width	mm	750	1150	1150
Dimensions	Depth	mm	620	620	620
	Weight	kg	21	28	28
Sound Pressure (Cooling)	High / Nom / Low	dBA	35/33/27	38/35/30	38/35/30
Sound Pressure (Heating)	High / Nom / Low	dBA	35/33/27	38/35/30	38/35/30
Sound Power (Cooling)		dBA	53	55	55

Outdoor Units			RZAG35A	RZAG50A	RZAG60A
Dimensions	Height x Width x Depth	mm	734 x 870 x 373	734 x 870 x 373	734 x 870 x 373
Weight		kg	52	52	52
Electrical Details	Power Supply		1ph	1ph	1ph
	Maximum Input Current (MCA)	A	14.53	15.23	17.10
	Max Fuse Size	A	16	16	20
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length	m	50	50	50
	Maximum Vertical Rise	m	30	30	30
	Precharged to	m	30	30	30
	Additional charge	g/m	20	20	20
	Holding charge	kg	1.55	1.55	1.55
Sound Pressure (Cooling)	Nominal	dBA	48	49	50
Sound Pressure (Heating)	Nominal	dBA	48	49	50
Sound Power (Cooling)		dBA	62	63	64
Operating Range (Cooling)	Min / Max	°CDB	-20 / +52	-20 / +52	-20 / +52
Operating Range (Heating)	Min / Max	°CWB	-20 / +24	-20 / +24	-20 / +24
Air Flow Rate (Cooling)	Nominal	m ³ /sec	0.918	0.918	0.918

Accessory Ref	Description
BRC1E53A	Premium wired remote controller (Included as standard)
BRP069A81	Wifi adaptor for connection to on-line controller
BRC1H519W	New - wired touch screen remote controller - White
BRC1H519S	New - wired touch screen remote controller - Silver
BRC1H519K	New - wired touch screen remote controller - Black
BRC2E52C	Wired simplified remote controller (without auto swing)
BRC4C65	Wireless remote controller
K.CGM	Condensing unit guard size 42-71
K.CGS	Condensing unit guard size 20-35
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2
K.RSS	Wireless room mounted temperature sensor and receiver
KLIC-DI	KNX Interface for Sky Air and VRV systems

Accessory Ref	Description
KRCS01-4	Remote room mounted temperature sensor
KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
RS-SE	Service and configuration tool for K.RSS
RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV. Duty rotation, Lead Lag control and heating interlock
RTD-20 and UK.FB2	Energy control PCB for Sky Air and VRV
RTD-NET and UK.FB2	Modbus interface PCB for Sky Air and VRV
UK.RAC5	Return Air Plenum for FDXM25/35F3
UK.RAC7	Return Air Plenum for FDXM50F3 and FDXM60F3
UK.SAF5	Supply Air Plenum for FDXM25/35F3
UK.SAF7	Supply Air Plenum for FDXM50F3 and FDXM60F3

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com